

## Dulux Prepcoat Acrylic Sealer Undercoat

NZDD0815

<b>Part A</b>	630-52934
<b>Approvals</b>	Environmental Choice Certified.






<b>Description</b>
DULUX Prepcoat Acrylic Sealer Undercoat is a premium interior water based acrylic sealer and undercoat. It has excellent opacity, dries hard for good sanding, fills timber grain well, and provides a smooth even surface for applying topcoats.

<b>Features</b>
<ul style="list-style-type: none"> <li>Provides a durable and uniform smooth surface for applying topcoats</li> <li>Universal &amp; multipurpose</li> <li>High opacity</li> <li>Ease of application</li> </ul>

<b>Benefits</b>
<ul style="list-style-type: none"> <li>Excellent high quality finish</li> <li>Can be used under either oil based or water based topcoats</li> <li>Good coverage</li> </ul>

<b>Uses</b>
DULUX Prepcoat Acrylic Sealer Undercoat is recommended over paperfaced plaster board (Gib), masonry, brick, and new interior timber.

<b>Performance Guide</b>			
<b>Weather</b>	Excellent as part of system using approved topcoat.	<b>Heat Resistance</b>	Resists temperatures up to 60 degrees.
<b>Water</b>	Resists mild & intermittent exposure to steam & condensation as part of system.	<b>Solvent</b>	Sensitive to aromatic hydrocarbons and alcohols.

<b>Typical Properties</b>																											
<b>Gloss Level</b>	Flat	<b>Thinner</b>	Water																								
<b>Colour</b>	White - can be tinted up to 1/2 strength of pastel colours.	<b>Components</b>	1																								
<b>Number Of Coats</b>	1	<b>Toxicity</b>	Lead free. Dry film is non-toxic.																								
<b>V.O.C. Level</b>	45	<b>Touch Dry</b>	20 Minutes																								
<b>Clean Up</b>	 Water																										
<b>Clean Up Description</b>	Clean all equipment immediately with water.																										
<b>Application Method</b>	    Air Spray    Airless Spray    Brush    Roller																										
<b>Application Conditions</b>	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;"><b>Solids By Volume</b></td> <td style="text-align: center;">39</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;"><b>Min</b></td> <td style="text-align: center;"><b>Max</b></td> <td style="text-align: center;"><b>Recommended</b></td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">79</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">31</td> </tr> <tr> <td>Recoat Time (min)</td> <td style="text-align: center;">2 Hours</td> <td></td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m<sup>2</sup>/L)</td> <td></td> <td></td> <td style="text-align: center;">12</td> </tr> </table>			<b>Solids By Volume</b>	39				<b>Min</b>	<b>Max</b>	<b>Recommended</b>	Wet Film Per Coat (microns)			79	Dry Film Per Coat (microns)			31	Recoat Time (min)	2 Hours			Theoretical Spread Rate (m <sup>2</sup> /L)			12
<b>Solids By Volume</b>	39																										
	<b>Min</b>	<b>Max</b>	<b>Recommended</b>																								
Wet Film Per Coat (microns)			79																								
Dry Film Per Coat (microns)			31																								
Recoat Time (min)	2 Hours																										
Theoretical Spread Rate (m <sup>2</sup> /L)			12																								

Application Guide	
<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>PREVIOUSLY PAINTED SURFACES Thoroughly clean all surfaces free of loose dust, surface chalk, grease, mould, mildew, wax, loose or flaking paint. Wash with sugar soap. Rinse with clean water. Fill nail holes and cracks with a suitable filler, sand smooth and dust off.</li> <li>NEW INTERIOR TIMBER Fill any nail holse, cracks, or imperfections with an appropriate filler. Sand smooth and dust off.</li> <li>PAPERFACED WALLBOARD, BRICK, MASONRY, FIBRO &amp; FIBRO CEMENT BOARD, &amp; CONCRETE Fill imperfections with a suitable filler, sand smooth and dust off. For fibrous or bare set plaster use Dulux Prepcoat Sealer Binder.</li> </ul>
<b>Application Procedure And Equipment</b>	<ul style="list-style-type: none"> <li>Brush, roller, conventional and airless spray.</li> <li>Stir contents thoroughly before and during use with a broad, flat stirrer using an upward lifting action.</li> </ul> <p>Brush/Roller: Pre-wet brushes and roller with water prior to use. A short or medium nap roller will give most uniform appearance. Apply a full even coat and finish by light parallel strokes with a practically dry roller.</p> <p>Conventional/Airless Spray: Suitable for application by all standard spray equipment.</p>

Health And Safety			
<b>MSDS Number</b>	4207	<b>Using Safety Precautions</b>	For detailed information refer to the product label and the current Material Safety Data Sheet available through Dulux NZ Sales and Customer Service offices.
<b>MSDS Link</b>	<a href="http://msds.duluxgroup.com/pdf/shess-en-cds-020-00000004207.pdf">http://msds.duluxgroup.com/pdf/shess-en-cds-020-00000004207.pdf</a>		
<b>Health Effects</b>	Splashes to the eye will cause eye irritation. When spraying, inhalation of mists and vapours may produce respiratory irritation and headaches.	<b>Protective Equipment</b>	Wear eye protection and when spraying or applying to broadwall areas wear a respirator with a combined vapour/particulate cartridge.
<b>Disposal</b>	Do not contaminate stormwater with product or product washings. Do not pour product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry, recycle the container via recycling programmes. Disposal of empty paint containers via recycling programmes may differ between local authorities. Check with your local council first.		
<b>In the case of emergency, please call 0800 734 607</b>			

Precautions And Limitations
Do not apply when the temperature is 10C or under or likely to fall below 10C during the drying period. Do not overspread, or exceed the recommended spreading rate.

Transport And Storage			
<b>Pack A</b>	630-52934	<b>Shipment Name</b>	Not dangerous goods.; No special transport requirements.
<b>Size</b>		<b>Weight</b>	
1 Litre		1.8Kg	
2 Litre		3.3Kg	
4 Litre		6.5Kg	
10 Litre		15.3Kg	
<b>Flash Point</b>	NA	<b>UN Number</b>	NA
<b>Dangerous Goods Class</b>	NA	<b>Package Group</b>	NA

**Disclaimer**

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118