

## Dulux Timbacryl Low Sheen

NZDD1268

<b>Part A</b>	554 LINE
<b>Approvals</b>	Environmental Choice Certified.






<b>Description</b>
DULUX Timbacryl is a long lasting exterior low sheen 100% acrylic paint.

<b>Features</b>
<ul style="list-style-type: none"> <li>• Water based</li> <li>• 100% acrylic paint</li> <li>• Tannin resistant formulae</li> <li>• Self priming</li> <li>• 10 Year Guarantee</li> </ul>

<b>Benefits</b>
<ul style="list-style-type: none"> <li>• Same day recoat and easy clean up</li> <li>• Proven excellent durability which maximises time before recoating</li> <li>• No Primer/Sealer required on timber to prevent staining</li> <li>• Apply direct onto most bare surfaces</li> <li>• Long Lasting</li> </ul>

<b>Uses</b>
Use DULUX Timbacryl over dressed and rough saw timbers, pergolas, decking, fences, fascia boards, timber furniture, bricks, masonry, fibre cement sheeting, Zinalume & galvanised iron. Dulux guarantees that Timbacryl will not blister, flake or peel for 10 years, provided it is applied on properly prepared surfaces as per label directions. This guarantee does not cover paint failure caused by any breakdown of coatings applied previously. If Dulux Timbacryl does not perform as specified above, Dulux will provide free of charge paint to rectify the affected areas.

<b>Performance Guide</b>			
<b>Weather</b>	Excellent resistance to weathering, with very low level of chalking, colour change and dirt pick up	<b>Salt</b>	Resists salt spray.
<b>Heat Resistance</b>	Softens at high temperatures, above 70C.	<b>Water</b>	Resists prolonged rain and condensation.
<b>Solvent</b>	Sensitive to aromatic hydrocarbons and alcohols.	<b>Abrasion</b>	Good resistance to abrasion.

Typical Properties																											
<b>Gloss Level</b>	5-15 at 60 degrees	<b>Thinner</b>	Water																								
<b>Colour</b>	Machine tinted to a full range of colours from an extensive range of white and coloured bases.	<b>Components</b>	1																								
<b>Number Of Coats</b>	2 or 3 depending on substrate condition	<b>Toxicity</b>	Lead free. Dry film is non-toxic.																								
<b>V.O.C. Level</b>	53 g/L	<b>Touch Dry</b>	20 Minutes																								
<b>Clean Up</b>	 Water																										
<b>Clean Up Description</b>	Clean all equipment with water.																										
<b>Application Method</b>	    Air Spray    Airless Spray    Brush    Roller																										
<b>Application Conditions</b>	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;"><b>Solids By Volume</b></td> <td style="text-align: center;">41</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;"><b>Min</b></td> <td style="text-align: center;"><b>Max</b></td> <td style="text-align: center;"><b>Recommended</b></td> </tr> <tr> <td><b>Wet Film Per Coat (microns)</b></td> <td></td> <td></td> <td style="text-align: center;">61</td> </tr> <tr> <td><b>Dry Film Per Coat (microns)</b></td> <td></td> <td></td> <td style="text-align: center;">25</td> </tr> <tr> <td><b>Recoat Time (min)</b></td> <td style="text-align: center;">2 Hours</td> <td style="text-align: center;">Indefinite</td> <td></td> </tr> <tr> <td><b>Theoretical Spread Rate (m<sup>2</sup>/L)</b></td> <td></td> <td></td> <td style="text-align: center;">16.4</td> </tr> </table>			<b>Solids By Volume</b>	41				<b>Min</b>	<b>Max</b>	<b>Recommended</b>	<b>Wet Film Per Coat (microns)</b>			61	<b>Dry Film Per Coat (microns)</b>			25	<b>Recoat Time (min)</b>	2 Hours	Indefinite		<b>Theoretical Spread Rate (m<sup>2</sup>/L)</b>			16.4
<b>Solids By Volume</b>	41																										
	<b>Min</b>	<b>Max</b>	<b>Recommended</b>																								
<b>Wet Film Per Coat (microns)</b>			61																								
<b>Dry Film Per Coat (microns)</b>			25																								
<b>Recoat Time (min)</b>	2 Hours	Indefinite																									
<b>Theoretical Spread Rate (m<sup>2</sup>/L)</b>			16.4																								

Application Guide	
<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>PRE-PRIMED TIMBER &amp; PREVIOUSLY PAINTED SURFACES Occasionally an apparently sound old paint will lose adhesion when recoated, particularly if the new paint is darker in colour. To avoid this, check the adhesion of the old paint by cutting an 'X' through a clean area of the film with a sharp knife, press cellulose tape firmly across the cut and rip it off. If the old paint comes off with the tape it should be removed before repainting. Scrape off all loose and flaking paint. Fill any cracks or holes with a suitable filler. Sand all surfaces to a flat finish and remove greyed timber. Dust off. Spot prime any bare areas with Dulux Timbacryl. Apply two generous coats of Dulux Timbacryl.</li> </ul> <p><b>TIMBER</b> Fill nail holes with a flexible, exterior grade woodfiller. Sand all dressed timber. Apply 3 coats of Dulux Timbacryl.</p> <p><b>BRICK, MASONRY, FIBRO &amp; FIBRE CEMENT BOARD</b> Unpainted masonry surfaces should be cured for 28 days before painting. Ensure surface is sound and clear of any loose sand or cement. Fill holes with a grouting cement. Wash down with water using a stiff brush to remove all loose material. To remove any efflorescence (white slats) wipe down with a 5% solution of acetic acid (white vinegar). Hose down and allow to dry. Wash with a bleach solution and/or demossing chemical to remove mould, or moss. The hose down. Apply 3 coats of Dulux Timbacryl.</p> <p><b>GALVANISED IRON</b> Clean with a Scotch Brite nylon pad and sugar soap solution. Thoroughly hose off. Apply 1 coat of Dulux Quit Rust All Metal Primer.</p> <p><b>PLASTIC SPOUTING &amp; DOWNPIPES</b> Sand all surfaces and dust off.</p> <p><b>STEEL/WROUGHT IRON</b> Remove all rust by scraping, sanding or wire brushing. Apply 2 coats of Dulux Quit Rust All Metal Primer.</p>
<b>Application Procedure And Equipment</b>	<ul style="list-style-type: none"> <li>Brush, roller, conventional or airless spray.</li> <li>Stir contents thoroughly before and during use with a broad flat stirrer, using an upward lifting action.</li> </ul> <p>Brush/Roller: Apply full even coats direct from the container. Under hot and very windy conditions up to 100 ml of DULUX Hot Weather Thinner may be added per litre to ease application.</p> <p>Airless/Conventional Spray: Suitable for application by all standard spray equipment. Apply wet even coats. If necessary thin with up to 100 ml of water per litre to aid atomisation.</p> <p>If required True Grip may be added to the final coat to aid slip resistance.</p>

Health And Safety			
<b>MSDS Number</b>	20919	<b>Using Safety Precautions</b>	For detailed information refer to the product label and the current Material Safety Data Sheet available through Dulux Sales and Customer Service offices.
<b>MSDS Link</b>	<a href="http://msds.duluxgroup.com/pdf/shess-en-cds-020-00000020919.pdf">http://msds.duluxgroup.com/pdf/shess-en-cds-020-00000020919.pdf</a>		
<b>Health Effects</b>	Splashes to the eye may cause eye irritation. When spraying, inhalation of mists may produce respiratory irritation.	<b>Protective Equipment</b>	Wear eye protection and when spraying wear a suitable mask.
<b>Disposal</b>	Do not contaminate stormwater with product or product washings. Do not pour product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry, recycle the container via recycling programmes. Disposal of empty paint containers via recycling programmes may differ between local authorities. Check with your local council first.		
<b>In the case of emergency, please call 0800 734 607</b>			

Precautions And Limitations
<p>Check the adhesion of old paint by cutting an 'X' through the film with a razor blade or trimming knife, press cellulose tape firmly across the cut and rip it off. If the old paint comes off with the tape it should be removed before painting.</p> <p>Occasionally when dew or condensation forms on a newly dried film a slight milky deposit will be observed on the film. This is quite normal and does not impair the performance. Simply hose or wipe it off with a damp rag.</p> <p>Do not paint at temperatures below 10 degrees or when the temperature may fall below 10 degrees during the drying period.</p> <p>Do not apply to roofs or surfaces used for the collection of drinking water.</p> <p>Caution - Check with your substrate manufacturer before painting colours of LRV&lt;40</p>

Transport And Storage			
<b>Pack A</b>	554 LINE	<b>Shipment Name</b>	Not dangerous goods.; No special transport requirements.
<b>Size</b>		<b>Weight</b>	
1 Litre		1.4Kg	
4 Litre		5.5Kg	
10 Litre		12.5Kg	
<b>Flash Point</b>	NA	<b>UN Number</b>	NA
<b>Dangerous Goods Class</b>	NA	<b>Package Group</b>	NA

**Disclaimer**  
Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118