

**Dulux Wash & Wear 101 Flat**

**NZDD1609**

<b>Part A</b>	577 LINE
<b>Approvals</b>	Environmental Choice Certified.






<b>Description</b>
Dulux Wash & Wear 101 has Barrier Technology™, which creates a super tough acrylic finish that allows you to wipe away most common marks and stains with a wet cloth. Dulux Wash & Wear Flat is low odour and low VOC.

<b>Features</b>
<ul style="list-style-type: none"> <li>• Water based</li> <li>• Tough acrylic finish</li> <li>• Flat finish</li> <li>• Low VOC &amp; low odour</li> </ul>

<b>Benefits</b>
<ul style="list-style-type: none"> <li>• Easy application, quick drying</li> <li>• Easy to clean.</li> <li>• Hides surface imperfections</li> <li>• Almost no paint smells</li> </ul>

<b>Uses</b>
Dulux Wash & Wear Flat is recommended for ceilings and walls in low traffic areas such as bedrooms. Suitable for use on properly prepared & primed/undercoated paper faced wall board (Gib® board) , cement, brick, interior timber, set plaster, fibrous plaster, plaster glass, & previously painted surfaces.

<b>Performance Guide</b>			
<b>Weather</b>	Not recommended for exterior use.	<b>Heat Resistance</b>	Up to 70C
<b>Water</b>	Not recommended for wet areas.	<b>Solvent</b>	Sensitive to aromatic hydrocarbons and alcohols.
<b>Abrasion</b>	Resists marring.		

Typical Properties																											
<b>Gloss Level</b>	0-2 at 60 degrees	<b>Thinner</b>	Water																								
<b>Colour</b>	Machine tint to a wide range of colours from an extensive range of bases.	<b>Components</b>	1																								
<b>Number Of Coats</b>	2	<b>Toxicity</b>	Lead free. Dry film is non-toxic.																								
<b>V.O.C. Level</b>	All bases <1 g/L	<b>Meets GBCA VOC Requirement?</b>	Yes. Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.																								
<b>Touch Dry</b>	30 Minutes																										
<b>Clean Up</b>	 Water																										
<b>Clean Up Description</b>	Clean all equipment with water.																										
<b>Application Method</b>	 Air Spray  Airless Spray  Brush  Roller																										
<b>Application Conditions</b>	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;"><b>Solids By Volume</b></td> <td style="text-align: center;">36</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;"><b>Min</b></td> <td style="text-align: center;"><b>Max</b></td> <td style="text-align: center;"><b>Recommended</b></td> </tr> <tr> <td><b>Wet Film Per Coat (microns)</b></td> <td></td> <td></td> <td style="text-align: center;">61</td> </tr> <tr> <td><b>Dry Film Per Coat (microns)</b></td> <td></td> <td></td> <td style="text-align: center;">22</td> </tr> <tr> <td><b>Recoat Time (min)</b></td> <td style="text-align: center;">2 Hours</td> <td style="text-align: center;">Indefinite</td> <td></td> </tr> <tr> <td><b>Theoretical Spread Rate (m<sup>2</sup>/L)</b></td> <td></td> <td></td> <td style="text-align: center;">16</td> </tr> </table>			<b>Solids By Volume</b>	36				<b>Min</b>	<b>Max</b>	<b>Recommended</b>	<b>Wet Film Per Coat (microns)</b>			61	<b>Dry Film Per Coat (microns)</b>			22	<b>Recoat Time (min)</b>	2 Hours	Indefinite		<b>Theoretical Spread Rate (m<sup>2</sup>/L)</b>			16
<b>Solids By Volume</b>	36																										
	<b>Min</b>	<b>Max</b>	<b>Recommended</b>																								
<b>Wet Film Per Coat (microns)</b>			61																								
<b>Dry Film Per Coat (microns)</b>			22																								
<b>Recoat Time (min)</b>	2 Hours	Indefinite																									
<b>Theoretical Spread Rate (m<sup>2</sup>/L)</b>			16																								

Application Guide	
<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>All surfaces must be thoroughly cleaned and free of all loose dirt, dust, grease, loose or flaking paint, and loose surface plaster. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces by thoroughly sanding and wipe clean with a damp cloth. Apply 1 coat of Dulux 1 Step Water Base.</li> </ul>
<b>Application Procedure And Equipment</b>	<ul style="list-style-type: none"> <li>Brush, roller, conventional and airless spray.</li> <li>Stir contents thoroughly before and during use with a broad flat stirrer using an upward lifting action.</li> </ul> <p>Brush/Roller: Use medium nap roller (10 - 15mm). Pre-wet brushes and roller with water before commencing application. Avoid excessive brushing or rolling back into the paint which has been drying for more than 3 minutes. Thinning not usually required. Under hot conditions application can be eased by thinning with up to 50mL water per litre and slightly dampening the surface. Apply two coats of Wash &amp; Wear Flat ensuring that the first coat is completely dry before applying the second.</p> <p>Airless/Conventional Spray: Suitable for application by all standard spray equipment. If necessary, to aid atomisation, up to 100 ml per litre of water may be added for conventional spray or up to 30 ml per litre of water for airless spray.</p>

Health And Safety			
<b>Using Safety Precautions</b>	For detailed information refer to the product label and the current Material Safety Data Sheet available through Dulux Sales and Customer Service offices.		
<b>MSDS Link</b>	<a href="http://msds.duluxgroup.com/pdf/shess-en-cds-020-00000010941.pdf">http://msds.duluxgroup.com/pdf/shess-en-cds-020-00000010941.pdf</a>		
<b>Health Effects</b>	Splashes to the eye may cause eye irritation. When spraying, inhalation of mists may produce respiratory irritation.	<b>Protective Equipment</b>	Wear eye protection and when spraying wear a suitable mask.
<b>Disposal</b>	Do not contaminate stormwater with product or product washings. Do not pour product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry, recycle the container via recycling programmes. Disposal of empty paint containers via recycling programmes may differ between local authorities. Check with your local council first.		
<b>In the case of emergency, please call 0800 734 607</b>			

Precautions And Limitations
Do not paint at temperatures below 10 °C or when the temperature of surface may fall below 10 °C during the drying period.
Do not paint if Relative Humidity is above 85% or temperature is within 3 °C of Dew Point
Avoid exposure to steam and condensation for at least 48 hours after application.
Dulux Wash & Wear Flat will reach its full mark resistance after one week. The surface can then be cleaned with a soft wet cloth. For more stubborn stains, use a wet cloth and cleaner such as Ajax Spray n' Wipe®.
Note: Some colours may require more than two coats to achieve full coverage, especially when painting over dark colours.

Transport And Storage			
<b>Pack A</b>	577 LINE	<b>Shipment Name</b>	Not dangerous goods.; No special transport requirements.
<b>Size</b>		<b>Weight</b>	
1 Litre		1.4Kg	
2 Litre		2.8Kg	
4 Litre		5.7Kg	
10 Litre		14Kg	
<b>Flash Point</b>	NA	<b>UN Number</b>	NA
<b>Dangerous Goods Class</b>	NA	<b>Package Group</b>	NA

**Disclaimer**

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.  
 DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118