

Dulux Professional Fast Finish Water Based Enamel Gloss

NZ_DD02321

Part A	56G-84179
---------------	-----------






Description
Premium, water based enamel that is ideal for doors, windows and trim. Can be used in most areas where traditional oil based enamels are used, with all the time saving benefits of an acrylic paint.

Features
<ul style="list-style-type: none"> ▪ Enamel like finish ▪ Fast drying ▪ Optimised for spray application ▪ Low odour

Benefits
Ideal for doors, windows and trim.

Uses
Suitable for interior and exterior use (doors, windows, trim).

Performance Guide			
Weather	Designed for interior and Exterior use.	Heat Resistance	Softens and sticks to other painted surfaces over 70C
Water	Suitable for use in wet areas	Solvent	Sensitive to aromatic hydrocarbons and alcohols
Abrasion	Good wet and dry burnish resistance and stain removal		

Typical Properties																											
Gloss Level	75 - 85 at 60 degrees	Thinner	Water																								
Colour	White & machine tinted to a wide range of colours from white.																										
Dulux Colour Base	VIVID WHITE																										
Components	1	Number Of Coats	2																								
V.O.C. Level	< 75 g/L	Touch Dry	30 mins																								
Clean Up	 Water																										
Clean Up Description	Clean all equipment with water.																										
Application Method	    Air Spray Airless Spray Brush Roller																										
Application Conditions	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Solids By Volume</td> <td style="text-align: center;">34.56</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td style="text-align: center;">62</td> <td style="text-align: center;">62</td> <td style="text-align: center;">62</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td style="text-align: center;">21</td> <td style="text-align: center;">21</td> <td style="text-align: center;">21</td> </tr> <tr> <td>Recoat Time (min)</td> <td style="text-align: center;">2 Hours</td> <td style="text-align: center;">Indefinite</td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td style="text-align: center;">16</td> <td style="text-align: center;">16</td> <td style="text-align: center;">16</td> </tr> </table>			Solids By Volume	34.56				Min	Max	Recommended	Wet Film Per Coat (microns)	62	62	62	Dry Film Per Coat (microns)	21	21	21	Recoat Time (min)	2 Hours	Indefinite		Theoretical Spread Rate (m²/L)	16	16	16
Solids By Volume	34.56																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)	62	62	62																								
Dry Film Per Coat (microns)	21	21	21																								
Recoat Time (min)	2 Hours	Indefinite																									
Theoretical Spread Rate (m²/L)	16	16	16																								
Typical Properties Notes	All preparation and painting must conform to AS2311: The Painting of Buildings. Do not use at temperatures below 10C, or when the temperature of surface may fall below 10C during the drying period. Avoid exposure to steam and condensation for 48 hours after application. Although the film is dry to touch in 30 minutes allow 7 days for film to fully cure before washing. Tinted Colours: Ensure that the paint is thoroughly shaken and stirred immediately after addition of tinter to the can and again before use.																										

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> Previously painted surfaces (except cement sheet) must be sanded to remove all loose, powdery and flaking paint. Wash down with sugar soap and rinse with clean water to remove any dirt, oil or grease. Treat any mould present on the surface with a bleach solution diluted 3 to 1 with water, then wash again with fresh water. Sand all gloss & semi-gloss surfaces to a dull finish. Fill any cracks or holes with a suitable filler, sand and dust off. Bare plasterboard or timber should be prepared by applying a suitable undercoat or primer.
Application Procedure And Equipment	<ul style="list-style-type: none"> Some colours may require more than the recommended number of coats to achieve full opacity. Brush, roller and spray Stir well before use with a wide (approx 25mm) flat stirrer in a circular, lifting motion. Apply two coats by brush, roller or spray allowing at least two hours drying time between coats. Airless Spray Advice: Tip size: 0.009– 0.011" Pressure: 1700–2300psi Thin as required up to 100ml of water per litre if necessary. For spray application Air-Assisted Airless or Airless thinning is recommended. Up to 5% by volume (ie. 50ml per litre) of Dulux Professional Hot Weather Thinner can be added on hot, dry or windy days to assist application and overspray blend-in on exterior surfaces.

Health And Safety			
MSDS Number	DLXNZLEN000961	Using Safety Precautions	Keep out of reach of children. Provide adequate ventilation. Keep windows and doors open during use and while drying. If spraying follow equipment guidelines and wear a suitable respirator.
MSDS Link	https://go.lupinsys.com/duluxgroup/harms/pm/088778b996747b2348296feb747d23f6-published/attachment/nz-sds.pdf		
Health Effects	If poisoning occurs, contact a Doctor or Poisons Information Centre (AUST 131 126; NZ 0800 764 766). If swallowed: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Eye contact: If in eyes, hold eyes open, flush with running water for at least 15 minutes. Skin contact: If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If inhaled: Remove from contaminated area. For further product or application advice or a Safety Data sheet contact Dulux Customer Service AUST 13 23 77, NZ 0800 800 424. EMERGENCY INFORMATION (ALL HOURS): AUST 1800 033 111; NZ 0800 734 607	Personal	Avoid contact with skin and eyes or breathing vapour and spray mist (dust). Wash hands after use.
Disposal	Do not pour leftover paint into drains and waterways. Unwanted paint should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collections. Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle the containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first. Alternatively, keep unwanted paint in sealed containers for disposal via chemical waste collections. For spills & disposal: Slippery when spilt; clean up immediately.	Other	DO NOT REUSE CONTAINER UNLESS THOROUGHLY DECONTAMINATED.
In the case of emergency, please call 0800 734 607			

Transport And Storage			
Pack A	56G 84179	Shipment Name	Not dangerous goods.; No special transport requirements
Size	10 Litres	Weight	13.24 kg
Flash Point	NA	UN Number	NA
Dangerous Goods Class	NA	Package Group	NA

Disclaimer

Dulux, Selleys and Other marks followed by © are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by © are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118